

BERGER
WORLDWIDE
 Since 1760



BERGER PAINTS INTERNATIONAL LIMITED.

Plot No. 37, Mbozi Road, Chang'ombe, Dar es Salaam, Tanzania. | Tel: +255 22 2860360/1 | Fax: +255 22 2863795
 Hotline: +255 688 000 777 | Email: info@bergerpaintsintl.com | Website: www.bergerpaintsintl.com
Arusha Branch: P.O. Box 13632, Arusha, Tanzania. | Tel: +255 27 544781 | Cell: +255 687 014017
Mwanza Branch: P.O. Box 1780, Mwanza, Tanzania. | Cell: +255 687 014006
Mbeya Branch: P.O. Box 718, Mbeya, Tanzania. | Cell: +255 687 014023 / 32


Robbialaac
...the Better Paint!

CONTRACTOR EMULSION



- Interior grade emulsion
- Good coverage
- Wash ability
- Smooth Finish
- 7-8 M²/ Litre





CONTRACTOR EMULSION ni rangi ya maji yenye kukidhi mahitaji ya kiuchumi kwa gharama nafuu, ni laini na ina mwonekano usiongara inapopakwa katika maeneo tofauti kama inavyopendekezwa na kitengo cha ufundi BERGER PAINTS.

Matumizi: Ni kwa ajili ya matumizi ya ndani.

Upatikanaji: Inapatikana katika rangi nyeupe na shedi tofauti tofauti kulingana na kitabu cha rangi cha BERGER.

Maandalizi ya eneo: Eneo linalopakwa rangi liwe safi na bila ya grease, tumia ROBBIALAAC ANTIFUNGAL WASH kwa kuulia wadudu aina ya fungus, tumia STUCCO PUTTY-INTERIOR kujazia nyufa na kunyoosha kuta, ili kupata matokeo mazuri zaidi tumia mpako mmoja wa ROBBIALAAC ACRYLIC PRIMER UNDERCOAT WHITE (INTERIOR) / ROBBIALAAC ACRYLIC BINDER CLEAR (INTERIOR) kisha paka CONTRACTOR EMULSION. Mpako mmoja, miwili au zaidi ya CONTRACTOR EMULSION, yaweza kupakwa ukiacha masaa matatu mpaka manne kila baada ya mpako. Kama eneo lako lilishapakwa rangi yafaa kuondoa rangi kisha fuata utaratibu uliolezwa hapo juu.

Jinsi ya Kuchanganya: Tumia maji masafi kwa kiwango cha 10% ya ujazo wa rangi.


Jinsi ya kupaka rangi: Kwa kutumia roller au brashi, kama eneo ni kubwa waweza pia tumia spray gun. Safisha roller/brashi na spray gun kwa kutumia maji masafi ya vuguvugu mara tu baada ya kumaliza kupiga rangi. Kausha vifaa vyote mara baada ya kuvisafisha.

Rangi Kumwagika na kuitupa: Kama ikitokea ajali ya rangi kumwagika, imwagie mchanga kisha izoe na kwenda kuitupa kulingana na sheria husika.

Kuhifadhi: Rangi inatakiwa kuhifadhiwa kwenye eneo lenye hewa ya kutosha na joto lisilozidi nyuzi 35 za sentigrade katika ndoo yake halisi.

Muda wa kutumika: Yafaa kutumika mwaka mmoja tangu tarehe ya kutengenezwa ikiwa katika ndoo yake halisi.

KWA MAELEZO ZAIDI KUHUSU RANGI HII REJEA KARATASI YENYE MAELEZO YA KINA NA KIUFUNDI TDS/MSDS



CONTRACTOR EMULSION is water based acrylic paint, proven to be very versatile and great for economical interior finish. It gives a smooth and excellent matt finish on various substrates as recommended by the BERGER PAINTS technical specifications.

Usage: Recommended for interior applications only with limited washability.

Availability: Is available in white and various shade range as per BERGER shade card.

Surface preparations: The surface to be painted needs to be clear of all grease, laitance and fungal growth. For best results use ROBBIALAAC ANTIFUNGAL WASH for effective preparation. STUCCO PUTTY-INTERIOR can be applied to fill all cracks and surface undulation for smooth surface. We recommend applying one coat of ROBBIALAAC ACRYLIC PRIMER UNDERCOAT WHITE (INTERIOR) / ROBBIALAAC ACRYLIC BINDER CLEAR (INTERIOR) to provide thorough binding of ROBBIALAAC - CONTRACTOR EMULSION top coat. Two to three coats of ROBBIALAAC - CONTRACTOR EMULSION can be applied as per required finish, giving three to four hours gap between coats. Painted surfaces that require refurbishing can be prepared by removing the flakey old paint and proceeding with the procedure described above.

Diluents and thinning recommendation: Soft water and to the extent of maximum of 10% of the paint.

Method of application: By roller/brush and if large areas are to be painted one can use suitable spray application. To keep the brush/roller and spray equipment in good condition for use, clean the same in Luke warm water and dry them immediately after application.

Spillage and disposal: In case of accidental spillage, cover it with inert material sand/saw dust and can be disposed as per local regulations.

Storage: The material is to be stored in well ventilated rooms at an ambient temperature not more than 35°C and in original containers.

FOR FURTHER INFORMATION ON THE PRODUCT PLEASE REFER TO THE TDS/MSDS