

BERGER WORLDWIDE Since 1760



BERGER PAINTS INTERNATIONAL LIMITED.

Plot No. 37, Mbozi Road, Chang'ombe, Dar es Salaam, Tanzania. | Tel: +255 22 2860360/1 | Fax: +255 22 2863795
 Hotline: +255 688 000 777 | Email: info@bergerpaintsintl.com | Website: www.bergerpaintsintl.com
Arusha Branch: P.O. Box 13632, Arusha, Tanzania. | Tel: +255 27 544781 | Cell: +255 687 014017
Mwanza Branch: P.O. Box 1780, Mwanza, Tanzania. | Cell: +255 687 014006
Mbeya Branch: P.O. Box 718, Mbeya, Tanzania. | Cell: +255 687 014023 / 32



PIONEERS OF VINYL SILK WASH N WEAR



- Premium quality water based acrylic paint
- extremely durable
- For luxurious interior finishes
- Available in Matt and Silk
- Excellent wash ability
- 8 to 10 m²/litre





WASH N WEAR ni rangi ya maji inayodumu zaidi na ubora wa hali ya juu, inayofaa zaidi kwa matumizi ya ndani. Ni rangi yenye mwonekano wa mn'garo pia inapatikana katika mwonekano wa kawaida inapopakwa maeneo tofauti kama inavyopendekezwa na kitengo cha ufundi BERGER PAINTS.

Matumizi: Ni kwa ajili ya matumizi ya ndani na ni rahisi kuisafisha inapochafuka na inavumilia mikwaruzo kwa muda mrefu.

Upatikanaji: Inapatikana katika rangi nyeupe na rangi tofauti kulingana na kitabu cha rangi cha BERGER na *Colorizer*.

Maandalizi ya eneo: Eneo linalopakwa rangi liwe safi na bila ya grease, tumia ROBBIALAAC ANTIFUNGAL WASH kwa kuulia wadudu aina ya fangas, tumia STUCCO PUTTY-INTERIOR kujazia nyufa na kunyoosha kuta ili kupata matokeo mazuri zaidi tumia mpako mmoja wa ROBBIALAAC ACRYLIC PRIMER UNDERCOAT WHITE (INTERIOR) / ROBBIALAAC ACRYLIC BINDER CLEAR (INTERIOR) kisha paka WASH N WEAR. Mpako mmoja, miwili au zaidi ya WASH N WEAR yaweza kupakwa ukiacha masaa matatu mpaka manne kila baada ya mpako. Kama eneo lako lilishapakwa rangi yafaa kutumia njia za kimakenika kuondoa rangi kisha fuata utaratibu uliolezwa hapo juu.

Jinsi ya Kuchanganya: Tumia maji masafi kwa kiwango cha 10% ya ujazo wa rangi.

Jinsi ya kupaka rangi: Kwa kutumia roller au brashi, kama eneo ni kubwa waweza tumia spray gun. Safisha roller/brashi na spray gun kwa kutumia maji masafi mara tu baada ya kumaliza kupiga rangi. Kausha vifaa vyote mara baada ya kuvisafisha.

Rangi Kumwagika na kuitupa: Kama ikitokea ajali ya rangi kumwagika, imwagie mchanga kisha izoe na kwenda kuitupa kulingana na sheria husika.

Kuhifadhi: Rangi inatakiwa kuhifadhiwa kwenye eneo lenye hewa ya kutosha na joto lisilozidi nyuzi 35 za sentigrade katika ndoo yake halisi.

Muda wa kutumika: Yafaa kutumika mwaka mmoja tangu tarehe ya kutengenezwa ikiwa katika ndoo yake halisi kabla kufunguliwa.

KWA MAELEZO ZAIDI KUHUSU RANGI HII REJEA KARATASI YENYE MAELEZO YA KINA NA KIUFUNDI TDS/MSDS



WASH N WEAR is a premium quality long lasting water based acrylic paint, used to achieve luxurious finishes. It gives an excellent sheen/matt finish on various substrates as recommended by the BERGER PAINTS technical specifications.

Usage: Recommended for interior usage only. It has good wash ability and can withstand some amount of scrub from stains of various types.

Availability: Is available in white and various shade range as per BERGER shade card and *Colorizer*.

Surface preparations: The surface to be painted needs to be clear of all grease, laitance and fungal growth. For best results use ROBBIALAAC ANTIFUNGAL WASH for effective preparation. STUCCO PUTTY-INTERIOR can be applied to fill all cracks and surface undulation for smooth surface. We recommend applying one coat of ROBBIALAAC ACRYLIC PRIMER UNDERCOAT WHITE (INTERIOR) / ROBBIALAAC ACRYLIC BINDER CLEAR (INTERIOR) to provide thorough binding of WASH N WEAR top coat. Two to three coats of WASH N WEAR can be applied as required, giving three to four hours gap between coats. Painted surfaces that require refurbishing can be prepared by removing the flakey old paint and proceeding with the procedure described above

Thinning recommendation: Soft water and to the extent of maximum of 10% of the paint.

Method of application: By roller/brush and if large areas are to be painted one can use suitable spray application. To keep the brush/roller and spray equipment in good condition for use, clean the same in Luke warm water and dry them immediately after application.

Spillage and disposal: In case of accidental spillage, cover it with inert material sand/saw dust and can be disposed as per local regulations.

Storage: The material is to be stored in well ventilated rooms at an ambient temperature not more than 35°C and in original containers.

Shelf Life: Best before one year from the date of manufacture in original sealed container. Identification labels convey all relevant matters.

FOR FURTHER INFORMATION ON THE PRODUCT PLEASE REFER TO THE TDS/MSDS